

DEPARTMENT OF HORTICULTURE

(Sri Karan Narendra Agriculture University: Johner) SKN College of Agriculture, Johner-303 329 (Jaipur)

No. RKVY/HORT/SKNCOA/2024/102

Date: 11.07.2024

Sealed limited tender are invited from the reputed firms for the supply of the Digital Refractometer, pH Conductivity and Temperature Meter, Fruit & Vegetable Penetrometer, Vernier Caliper and Chlorophyll Meter and details of which are given below. The tender quotations will be accepted up to 11.00 AM on 19.07.2024 and will be opened at 11.30 AM on the same day in the Department of Horticulture. The committee has all right to accept/reject tender any reasons. All goods are F.O.R. at Department of Horticulture. The tender will be submitted along with a bank 4000/- in favor of Dean, SKNCOA, Jobner. The approximate cost purchasing can be increased /decreased.

nder	any reasons. All goods are 1.0.1c. at 214 f Rs.4000/- in favor of Dean, SKNCOA, Jobner. The approximate cost purchasing can be increased for the second sec	Quantity		
ran o	Name of item with specification	01 Nos.		
1.	Digital Refractometer with Automatic Temperature Compensation, LED diplay,			
	0 to 50 PSII -2 PSU Accuracy, 1130 Resolution	01 Nos.		
2.	Digital pH Conductivity and Temperature Meets Specifications: Source frequency (100Hz or KHz automatically selected), Temperature (0°C to			
	100°C), Display (3digits LED), Resolution conductivity Range (0 uS-200 mS) and Accessories			
	(1 Cell Constant Cell, Clam & Stand)	01 Nos.		
3	Digital fruit & vegetable Penetrometer Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen 2 Probes 7.9mm / 11.1mm, Pressure head Specifications: Digital Penetrometer, With LCD screen			
	large screen display	01 Nos.		
4	Digital Vernier Calliper Specifications: Accuracy: Resolution: 0.01mmor 0.0005"/0.01mm, Repeatability: 0.01mm/.0005", Display: LCD, Length standard: absolute electrostatic capacitancety pelinearen coder, Max. response speed: Unlimited, Battery: SR44 (1 pc.), 938882, Battery life: Approx. 3.0			
	years under normal use	01 Nos.		
5	Digital Chlorophyll Tester Meter Specifications: Measurement range: 0.0-100 SPAD & area: 2mm* 2mm, Measurement Specifications: Measurement range: 0.0-50.0 SPAD under normal temperature and humidity)	a		
	Repeatability within + 0.3 SPAD units (0.0-50.0 SPAD measurement position directions). Repeatability within + 0.3 SPAD units (0.0-50.0 SPAD measurement position directions). Space and support a storage medium: SD card & pen drive 4GB storage, data storage capacity: 2GB, Power: 4.2V storage medium: SD card & pen drive 4GB storage, data storage capacity: 2GB, Power: 4.2V rechargeable lithium battery, Battery capacity: 800MAH, Weight: 260g, Product Size: 140 x 85 x rechargeable lithium battery, Battery capacity: 800MAH, weight: 260g, Product Size: 140 x 85 x rechargeable lithium battery, Battery capacity: 800MAH, weight: 260g, Product Size: 140 x 85 x rechargeable lithium battery, Battery capacity: 800MAH, weight: 260g, Product Size: 140 x 85 x rechargeable lithium battery, Battery capacity: 800MAH, weight: 260g, Product Size: 140 x 85 x rechargeable lithium battery, Battery capacity: 800MAH, weight: 260g, Product Size: 140 x 85 x rechargeable lithium battery, Battery capacity: 800MAH, weight: 260g, Product Size: 140 x 85 x rechargeable lithium battery, Battery capacity: 800MAH, weight: 260g, Product Size: 140 x 85 x rechargeable lithium battery, Battery capacity: 800MAH, weight: 260g, Product Size: 140 x 85 x rechargeable lithium battery, Battery capacity: 800MAH, weight: 260g, Product Size: 140 x 85 x rechargeable lithium battery, Battery capacity: 800MAH, weight: 260g, Product Size: 140 x 85 x rechargeable lithium battery, Battery capacity: 800MAH, weight: 260g, Product Size: 140 x 85 x rechargeable lithium battery, Battery capacity: 800MAH, weight: 260g, Product Size: 140 x 85 x rechargeable lithium battery, Battery capacity: 800MAH, weight: 800MAH,	X		

Interested firms may quote their rate in the attached proforma and submit their tender to the undersigned in the sealed envelope.

Terms and conditions:

- 1. Brochure of item should be attached with tender document.
- The rates quoting firm should have GST number.
- The responsibility of GST/other charges etc. as per Government rule will be borne by supplier.
- Two year onsite warranty
- The firm should clearly mention the brand name and traditional name of the item.

PI (RKVY-37)

Copy to:

- 1. The Dean, SKNCOA, Jobner for kind information
- The Convenor/member Tender committee, SKNCOA, Johner
- A.A.O., SKNCOA, Jobner
- Incharge CIMCA with request to upload on University website
- Notice board, SKNCOA, Johner

PROPOSED RATES

	Name of item with specification	Proposed	GST	Total
S.	Name of item with specification	Rate		*
No.		8 12	*	*
1.	Digital Refractometer			
	Specifications: Digital Refractometer with Automatic Temperature Compensation, LED diplay, 0 to 50 PSU, -2 PSU Accuracy, 1 PSU			
	Compensation, LED diplay, 0 to 30 FSO, -2 150 Recuracy, 1 150			
	Resolution Motor			
2.	Digital pH Conductivity and Temperature Meter			
	Specifications: Source frequency (100Hz or KHz automatically selected), Temperature (0°C to 100°C), Display (3digits LED),			
	Resolution conductivity (0.1uS), Accuracy (+/-0.25% of f.s. +/-1			
	Digit), Dimension (W230xD180xH75 mm), Conductivity Range (0			
	uS-200 mS) and Accessories (1 Cell Constant Cell, Clam & Stand).		(W)	ω.
	us-200 ms) and Accessories (1 cen constant con, chair es state).			
3	Digital fruit & vegetable Penetrometer Specifications: Digital Penetrometer, With LCD screen 2 Probes			
	7.9mm / 11.1mm, Pressure head diameter: 1"diameter 11.1 mm – 2"			
	diameter 7.9 mm, Range: 0.2 - 15 Kg/cm², Precision (±1%), Indication		,	
	error (±0.5%), Automation Grade: Semi-Automatic, Display mode:			
	Digital, Six-figure large screen display			
	Digital Vernier Calliper			
4	Specifications: Accuracy: Resolution: 0.01mmor 0.0005"/0.01mm,	7 2		****
	Repeatability: 0.01mm/.0005", Display: LCD, Length standard:			
	absolute electrostatic canacitancety pelinearen coder, Max. response			
	speed: Unlimited, Battery: SR44 (1 pc.), 938882, Battery life:			
	Approx. 3.0 years under normal use			
5	Digital Chlorophyll Tester Meter			
3	Specifications: Measurement range: 0.0-100 SPAD & area: 2mm*		2	
	2mm Measurement accuracy: within 1 SPAD units (0.0-50.0 SPAD	'		
*	under normal temperature and humidity). Repeatability Within + 0.3)		
	SPAD units (0.0-50.0 SPAD measurement position unchanged), data	i		
	storage medium: SD card & pen drive 4GB storage, data storage	2		
	consists: 2GB Power: 42V rechargeable lithium battery, Battery	/		5
	capacity: 800MAH Weight: 260g, Product Size: 140 x 85 x 45mm	,		
	Working and storage environment: 0 -50°C, 85% relative humidity			

Signature of authorized person

Name of firm with full address

GST Number (Attach certificate)

Bank details (Bank name, account No., branch name& IFSC code)